

船用填料函

Marine Cable Gland-TJ Clamping Type





TJ

CE ROHS IP68 REACH

材质: 镀铬黄铜
密封件: 丁腈橡胶、硅橡胶
防水圈: 丁腈橡胶、硅橡胶
垫圈: 镀锌铁环
防水等级: IP54
工作温度: 静态: -40°C到 100°C, 短时间达 120°C
动态: -20°C到 80°C, 短时间达 100°C

Material: Chromium-plated brass
Hermetic seal: NBR, Silicone rubber
O-Ring: NBR, Silicone rubber
Metal Washer: Nickel-plated hoop
Protection degree: IP54
Temperature: Static state: -40°C to 100°C, Short time to 120°C; Dynamic state: -20°C to 80°C, Short time to 100°C



规格参数 单位: mm

规格 Item	适用范围 Φ Range	螺纹规格 Thread		螺纹长度 H1 Thread Length	主体外径 D1 Body Outer Diameter	接合长度 H Joint Length	扳手径 ψ Spanner size	产品编号 Code
		D	d1					
TJ 8	5-7	M16×1	M14×1	9	19	32	18	HX-TJ8
TJ 13	6-12	M20×1	M18×1	10	24	35	22	HX-TJ13
TJ 16	11-15	M27×1.5	M22×1.5	12	31	40	30	HX-TJ16
TJ 19	14-18	M30×1.5	M27×1.5	12	34.5	42	32	HX-TJ19
TJ 24	17-23	M35×1.5	M30×1.5	12	40	44	36	HX-TJ24
TJ 28	22-27	M42×2	M36×1.5	15	46.5	46	45	HX-TJ28
TJ 34	26-33	M47×2	M42×2	15	54	49	50	HX-TJ34
TJ 42	32-41	M55×2	M52×2	15	60	54	57/59	HX-TJ42
TJ 50	40-49	M62×2	M58×2	15	69	56	64/68	HX-TJ50
TJ 58	48-57	M71×2	M68×2	20	77.5	56	76	HX-TJ58



船用填料函 Marine Cable Gland Series