

金属扩增环

Metal Enlarger




M / PG

CE ROHS

材质: 镀镍黄铜
 防水圈: 丁腈橡胶、硅橡胶
 防水等级: IP54
 工作温度: 静态: -40°C到 100°C, 短时间达 120°C

Material: Nickel-plated brass
 O-Ring: NBR, Silicone rubber
 Protection degree: IP54
 Temperature: Static state: -40°C to 100°C
 short time to 120°C



六角
Hexagonal



圆形
Round

规格 Item	螺纹 Thread		螺纹长度 GL	高度 H Joint Length	扳手径 ψ Spanner size	产品编号 Code
	Outer	Inner				
M12-M16	M12 X 1.5	M16 X 1.5	5	10.5	18	HX-REM12-M16
M16-M20	M16 X 1.5	M20 X 1.5	5	10.5	22	HX-REM16-M20
M20-M25	M20 X 1.5	M25 X 1.5	6	11.5	27	HX-REM20-M25
M25-M32	M25 X 1.5	M32 X 1.5	7	12	34	HX-REM25-M32
M32-M40	M32 X 1.5	M40 X 1.5	7	13	42	HX-REM32-M40
M40-M50	M40 X 1.5	M50 X 1.5	8	16	52	HX-REM40-M50
M50-M63	M50 X 1.5	M63 X 1.5	9	17	66	HX-REM50-M63
PG7-PG9	PG7	PG9	6	10.5	17	HX-REPG7-PG9
PG9-PG11	PG9	PG11	6.5	10.5	20	HX-REPG9-PG11
PG11-PG13.5	PG11	PG13.5	6.5	10.5	22	HX-REPG11-PG13.5
PG13.5-PG16	PG13.5	PG16	6.5	11	24	HX-REPG13.5-PG16
PG16-PG21	PG16	PG21	7.5	11	30	HX-REPG16-PG21
PG21-PG29	PG21	PG29	8	11	39	HX-REPG21-PG29
PG29-PG36	PG29	PG36	9	13	50	HX-REPG29-PG36
PG36-PG42	PG36	PG42	10	15	57	HX-REPG36-PG42
PG42-PG48	PG42	PG48	10	16	64	HX-REPG42-PG48

其他系列
Other Matched Accessories

