

## 单压缩式填料函



Single Compression Type Cable Gland



DCG **CE ROHS IP68 REACH**

材质: 镀镍黄铜  
 密封件: 丁腈橡胶、硅橡胶  
 防水圈: 丁腈橡胶、硅橡胶  
 垫圈: 镀锌铁环  
 防水等级: IP54  
 工作温度: 静态: -40℃到 100℃, 短时间达 120℃  
 动态: -20℃到 80℃, 短时间达 100℃

Material: Nickel-plated brass  
 Hermetic seal: NBR, Silicone rubber  
 O-Ring: NBR, Silicone rubber  
 Metal Washer: Nickel-plated hoop  
 Protection degree: IP54  
 Temperature: Static state: -40℃ to 100℃, Short time to 120℃; Dynamic state: -20℃ to 80℃, Short time to 100℃



规格参数 单位: mm

规格 Item	螺纹 Thread	适用范围 Φ Range	螺纹长度 GL Thread Length	螺纹外径 AG Thread O.D.	接合长度 H Joint Length	扳手径 ψ Spanner size	产品编号 Code
DCG7	PG7	5-6.5	5.0	12.5	16.5	14/15	HX-DCG7
DCG9	PG9	6-8	6.2	15.2	17.5	16/18	HX-DCG9
DCG11	PG11	8-11	6.5	18.6	17.5	20/21	HX-DCG11
DCG13.5	PG13.5	9-11.5	7.5	20.4	20.5	22/23	HX-DCG13.5
DCG16	PG16	11-14	8.0	22.5	22.2	24/26	HX-DCG16
DCG21	PG21	15-17.5	8.0	28.3	23.5	30/32	HX-DCG21
DCG29	PG29	20-23	8.0	37.0	25.5	40/41	HX-DCG29
DCG36	PG36	29-31	10.0	47.0	29.0	50/52	HX-DCG36
DCG42	PG42	32-38	11.0	54.0	33.0	57/57	HX-DCG42
DCG48	PG48	37-44	12.0	59.3	34.0	64/64	HX-DCG48



船用电缆系列 Marine Cable Gland Series