



Hoonsun
Fifteen years for only one thing!

防水接线盒

Waterproof Junction Box-RA series





防水接线盒

Waterproof Junction Box-RA series



RA / B 系列


CE ROHS

壳体材料：ABS
孔塞材料：PVC
材料特性：抗冲击性，耐热性，耐低温性，耐化学药品性及电气性能优良，表面光泽性好等特点
认证：CE、ROHS
用途：适用于室内，室外电气，通信，消防设备，钢铁冶炼，石油化工，电子电力，铁路，建筑工地，采矿场，机场，宾馆，船舶，大型工厂，沿海工厂，卸货码头设备，污水处理设施，环境公害设施等。
安装方式：1，内部安装：盒子内部有供线路板或 DIN 轨道元件安装的凸台；
2，外部安装：可通过盒体底部的安装孔直接固定于墙面（可通过盒子的四个角，直接用螺丝钉钉子在墙上货板子上。）
进出线孔：1：HXB-R-A 防水盒可以根据（是否穿线选择开孔。电线大小在现有孔塞上选择使用，或配套防水夹紧接头，达到防水最佳效果。
2：HXB-R-B 防水盒可以根据电线大小在现有孔塞上选择使用，或配套防水夹紧接头，达到防水最佳效果。

Body material : ABS
Stopper material : PVC
Material characteristics: Impact,heat,low temperature and chemical resistance,excellent electrical performance and surface gloss,etc.
Certificates:CE,ROHS
Protection grade:IP65
Application:Suitable for indoor and outdoor electric,communication,fire fighting apparatus,iron and steel smelting,petrochemical industry,electron,power system ,railway,building,mine,air and sea port,hotel,ship,works,waste water treatment equipment,environment equipment and so on.
Installation:1.Inside:There are the installation holes in the base for circuit board or din rail(More than 2 pcs of M4 brass nuts have been in the base).
2.Outside: The products can be directly fixed on the wall or other flat boards with screws or nails via the screw holes in the base.
Outlet hole:1 : Holes can be opened or not on the box as customers' requirements ,and installing cable gland can bring with better waterproof performance.
2.: Holes can be chosen according to the cable diameter from the existing holes on the box ,and installing cable gland can bring with better waterproof performance.

规格参数 单位: mm

型号 Model Code	孔数 Hole QTY	孔径 (mm) Hole Size	IP	毛重(KG) G. Weight	净重 (KG) G. Weight	装箱数 (只) Qty/Carton	外箱尺寸 (cm) Carton Dimension
HXB-RA/B 50x50	4	25	55	13.5	12.3	300	46*38*51
HXB-RA/B 80x50	4	25	55	14.7	13.4	240	53*35*62
HXB-RA/B 85x85x50	7	25	55	17.2	16	200	53*41*53
HXB-RA/B100x100x70	7	25	65	14.9	13.5	100	62*49*35
HXB-RA/B150x110x70	10	25	65	15.1	13.8	60	67*33*46.5
HXB-RA/B150x150x70	8	25	65	16.3	15	60	84.5*34*45
HXB-RA/B200x100x70	8	25	65	16.6	15.3	60	61*46*42
HXB-RA/B200x155x80	10	36	65	14.5	13.2	40	69.5*43.5*42
HXB-RA/B200x200x80	12	36	65	18	16.6	40	90*46*40.5
HXB-RA/B255x200x80	12	36	65	21.9	20.1	40	55*45*78.5
HXB-RA/B255x200x120	12	36	65	21.9	20.1	30	64*55*62
HXB-RA/B300x250x120	12	36	65	20.3	18.4	20	61.5*55.5*63
HXB-RA/B400x320x120	16	36	65	15	13.3	10	74.5*42.5*61.5



防水接线盒

Waterproof Junction Box-KT-seires



KT 系列


CE ROHS

壳体材料: ABS 或 PC
材料特性: 抗冲击性、耐热性、耐低温性、耐化学药品性及电气性能优良、表面光泽性好等特点
认证: CE、ROHS
防护等级: IP65
用途: 适用于室内、室外电气、通信、消防设备、钢铁冶炼、石油化工、电子、电力、铁路、建筑工地、采矿场、机场、宾馆、船舶、大型工厂、沿海工厂、卸货码头设备、污水处理设施、环境公害设施等。
安装方式: 1. 内部安装: 盒子内部有供线路板或 DIN 轨道元件安装的凸台, 及自带的铜接线螺母 (每只防水盒内部都配有最少二个以上的很常规的 M4 的铜螺母)
2. 外部安装: 可通过盒体底部的安装孔直接固定于墙面 (可通过盒子的四个角, 直接用螺丝或钉子固定在墙上或板子上)。
进出线孔: 防水盒可以随意根据客户的使用要求在上面开孔 (开孔位置及开孔大小都可以按照客户指定要求加工)。开孔后可以装有配套的防水紧接头, 达到防水最佳效果。

Body material: ABS or PC
Material characteristics: Impact, heat, low temperature and chemical resistance, excellent electrical performance and surface gloss, etc.
Certificates: CE, ROHS
Protection grade: IP65
Application: Suitable for indoor and outdoor electric, communication, fire fighting apparatus, iron and steel smelting, petrochemical industry, electron, power system, railway, building, mine, air and sea port, hotel, ship, works, waste water treatment equipment, environment equipment and so on.
Installation: 1. Inside: There are the installation holes in the base for circuit board or din rail (More than 2 pcs of M4 brass nuts have been in the base).
2. Outside: The products can be directly fixed on the wall or other flat boards with screws or nails via the screw holes in the base.
Outlet hole: Holes can be opened on the box as customers' requirements, and installing cable gland can bring with better waterproof performance.

规格参数 单位: mm

型号 Model Code	毛重 (KG) G. Weight	装箱数 (只) Qty/Carton	外箱尺寸 (cm) Carton Dimension	型号 Model Code	毛重 (KG) G. Weight	装箱数 (只) Qty/Carton	外箱尺寸 (cm) Carton Dimension
HXB-KT 65×50×55	21.5/20.0	300	52×41×29.5	HX-KT 200×150×130	21.6/20.1	40	61.5×41×68.5
HXB-KT 96×65×55	25.1/23.6	240	49.5×40.5×46.5	HX-KT 200×200×95	18.5/17.0	30	62×42×49.5
HXB-KT 100×100×75	20.4/18.9	100	52×42×39.5	HX-KT 200×200×130	14.6/13.1	20	42×42×67
HXB-KT 110×80×45	24.3/22.8	200	46×42×47	HX-KT 250×80×70	15.7/14.2	50	52×41×36
HXB-KT 110×80×70	20.0/18.5	120	57×33.5×45	HX-KT 250×80×85	18.8/17.3	50	52×42×44.5
HXB-KT 110×80×85	19.7/18.2	100	57×33.5×45	HX-KT 250×150×100	11.5/10.0	20	52×32×52
HXB-KT 125×125×75	16.6/15.1	60	52×39.5×39.5	HX-KT 250×150×130	17.1/15.6	30	52×47×67
HXB-KT 125×125×100	19.4/17.9	60	52×39.5×52	HX-KT 280×190×130	10.6/9.1	10	40×30×67
HXB-KT 130×80×70	21.4/19.9	120	54×41.5×45	HX-KT 280×190×180	14.5/13.0	12	58×40×56
HXB-KT 130×80×85	25.4/23.9	120	54×50×44.5	HX-KT 280×280×130	8.6/7.1	6	58×58×41
HXB-KT 160×80×55		100	42×34×57	HX-KT 280×280×180	9.6/8.1	6	58×58×56
HXB-KT 160×80×95		50	42×34×49.5	HX-KT 340×280×130	9.5/8.1	6	57.5×35×41
HXB-KT 170×140×95	17.8/16.3	50	57.5×52×49.5	HX-KT 340×280×180	7.9/6.4	4	57.5×35×37.5
HXB-KT 175×125×75	17.0/15.5	50	54×52.5×32	HX-KT 340×190×130	10.9/9.4	8	40×40×54
HXB-KT 175×125×100	11.9/10.4	30	39.5×37×52	HX-KT 380×190×180	12.5/11	6	40×59×38
HXB-KT 175×175×100	14.4/12.9	30	54.5×37×53.5	HX-KT 380×280×130	9.8/8.3	6	57.5×39×41
HXB-KT 180×80×70	20.4/18.9	90	56×41×46	HX-KT 380×280×180	8.0/6.5	4	57.5×39×37.5
HXB-KT 200×150×100	28.5/27	30	47×42×67				



壳体材料: ABS 或 PC
材料特性: 抗冲击性、耐热性、耐低温性、耐化学药品性及电气性能优良、表面光泽性好等特点
认证: CE、ROHS
防护等级: IP65
用途: 适用于室内、室外电气、通信、消防设备、钢铁冶炼、石油化工、电子、电力、铁路、建筑工地、采矿场、机场、宾馆、船舶、大型工厂、沿海工厂、卸货码头设备、污废水处理设施、环境公害设施等。
安装方式: 1. 内部安装: 盒子内部有供线路板或 DIN 轨道元件安装的凸台, 及自带的铜接线螺母 (每只防水盒内部都配有最少二个以上的很常规的 M4 的铜螺母)
2. 外部安装: 可通过盒体底部的安装孔直接固定于墙面 (可通过盒子的四个角, 直接用螺丝或钉子固定在墙上或板上)。
进出线孔: 防水盒可以随意根据客户的使用要求在上面开孔 (开孔位置及开孔大小都可以按照客户指定要求加工)。开孔后可以装有配套的防水紧接头, 达到防水最佳效果。

Body material: ABS or PC
Material characteristics: Impact, heat, low temperature and chemical resistance, excellent electrical performance and surface gloss, etc.
Certificates: CE, ROHS
Protection grade: IP65
Application: Suitable for indoor and outdoor electric, communication, fire fighting apparatus, iron and steel smelting, petrochemical industry, electron, power system, railway, building, mine, air and sea port, hotel, ship, works, waste water treatment equipment, environment equipment and so on.
Installation: 1. Inside: There are the installation holes in the base for circuit board or din rail (More than 2 pcs of M4 brass nuts have been in the base).
2. Outside: The products can be directly fixed on the wall or other flat boards with screws or nails via the screw holes in the base.
Outlet hole: Holes can be opened on the box as customers' requirements, and installing cable gland can bring with better waterproof performance.

规格参数

型号 Model Code	毛重 (KG) G. Weight	净重 (KG) G. Weight	装箱数 (只) Qty/Carton	外箱尺寸 (cm) Carton Dimension
HXB-GT 300×200×160	12.9	11.4	8	60×46×32
HXB-GT 300×200×180	13.4	11.9	8	64.5×40.5×54
HXB-GT 300×200×180	13.8	12.3	6	61.5×34×56.5
HXB-GT 400×300×180	17	15.5	6	66×41×56.5
HXB-GT 500×400×200	13.5	12	3	51×44×63
HXB-GT 600×400×220	17.5	16	3	61.5×41×68.5



MS 系列

CE ROHS

壳体材料: ABS

透明门板: PC

接线端子：铜

材料特性：抗冲击性、耐热性、耐低温性、耐化学药品性及电气性能优良、表面光泽性好等特点

认证: CE、ROHS

防护等级: IP50

用途: 适用于室内、室外电气、通信、消防设备、钢铁冶炼、石油化工、电子、电力、铁路、建筑工地、采矿场、机场、宾馆、船舶、大型工厂、沿海工厂、卸货码头设备、污水处理设施、环境公害设施等。

安装方式: 可选择明装或者暗装

1. 内部安装：盒子内部有供导轨式断路器安装的导轨，及用于接线的零线排和地线排。

2. 外部安装: 可通过盒体底部的安装孔直接固定于墙面(可通过盒子的四个角, 直接用螺丝或钉子固定在墙上或板子上)。

进出线孔：箱体设有可供穿线的预留孔。

Body material:ABS

Transparent door:PC

Earth/Natural bars:Brass

Material characteristics: Impact,heat,low temperature and chemical resistance,excellent electrical performance and surface gloss,etc.

Certificates:CE,ROHS

Protection grade:IP50

Application: Suitable for indoor and outdoor electric, communication, fire fighting apparatus, iron and steel smelting, petrochemical industry, electron, power system, railway, building, mine, air and sea port, hotel, ship, works, waste water treatment equipment, environment equipment had so on.

Installation:1.Inside:There are din rail inside for din-rail type circuit breakers,earth bar and natural bar for cable connection.

2.Outside: The products can be directly fixed on the wall or other flat boards with screws or nails via the screw holes in the base.

Outlet hole: The plastic plate in the hole can be knocked off for cables.

规格参数 单位: mm

型号 Model Code	外形尺寸 Outside Dimension(mm)			毛重 (KG) G. Weight	净重 (KG) G. Weight	装箱数 (只) Qty/Carton	外箱尺寸 (cm) Carton Dimension
	L	W	H				
HXB-MS 4WAY	112	200	95	11.5	8.7	30	51×36×45.5
HXB-MS 6WAY	148	200	95	14.9	11.5	30	51×42.5×50
HXB-MS 8WAY	184	200	95	16.7	12.8	30	52×43.5×59.5
HXB-MS 10WAY	222	200	95	13	9.8	20	51×43×48.5
HXB-MS 12WAY	256	200	95	14.8	11.5	20	52×43×55
HXB-MS 15WAY	310	200	95	12.8	9.9	15	50.5×33.5×64
HXB-MS 18WAY	365	222	95	15.2	12.8	15	52×38×71
HXB-MS 24WAY	271	325	97	13.2	10.3	10	55×35×57.5
HXB-MS 36WAY	271	462	100	18.5	14.8	5	54.5×28.5×48

