


金属加长型电缆接头
Metal Cable Gland- Length Type



M / PG

材质：镍镀黄铜
夹紧爪：尼龙塑料 PA66, UL94-V2
密封件：三元乙丙、硅橡胶等
防水圈：三元乙丙、硅橡胶等
防水等级：IP68-10 巴压力
工作温度：静态：-40℃到 100℃, 短时间达 120℃
动态：-20℃到 80℃, 短时间达 100℃

Material: Nickel-plated brass
Claw: IPAG66 (Nylon), UL94-V2
Hermetic seal: EPDM, Silicone rubber
O-Ring: EPDM, Silicone rubber
Protection degree: IP68-10 bar
Temperature: Static state: -40 to 100°C, Short time to 120°C
Dynamic state: -20°C to 80°C, Short time to 100°C



规格参数 单位: mm

专利产品
patented product

规格 Item	适用范围 Φ Range	螺纹长度 GL Thread Length	螺纹外径 AG Thread O.D.	接合长度 H Joint Length	扳手径 Spanner size	产品编号 Code
M12×1.5	3-6.5	10	12	17	14	HX-NP.M12 L10
M16×1.5	4-8	12	16	19	18	HX-NP.M16 L12
M18×1.5	5-10	12	18	21	20	HX-NP.M18 L12
M20×1.5	6-12	12	20	22	22	HX-NP.M20 L12
M22×1.5	10-14	12	22	23	24	HX-NP.M22 L12
M25×1.5	10-14	12	25	25	24/27	HX-NP.M25-14 L12
M25×1.5	13-18	12	25	27	30/27	HX-NP.M25-18 L12
M32×1.5	15-22	15	32	29	35	HX-NP.M32 L15
M40×1.5	18-25	15	40	31	40/45	HX-NP.M40-25 L15
M40×1.5	22-30	15	40	35	45	HX-NP.M40-30 L15
M50×1.5	32-38	15	50	37	57/55	HX-NP.M50 L15
M63×1.5	37-44	18	63	38	64/68	HX-NP.M63 L18
PG7	3-6.5	10	12.5	17	14/15	HX-NP.PG7 L10
PG9	4-8	12	15.2	19	17/18	HX-NP.PG9 L12
PG11	5-10	12	18.6	21	20/21	HX-NP.PG11 L12
PG13.5	6-12	12	20.4	22	22/23	HX-NP.PG13.5 L12
PG16	10-14	12	22.5	23	24/25	HX-NP.PG16 L12
PG21	13-18	12	28.3	27	30	HX-NP.PG21 L12
PG29	18-25	15	37.0	31	40	HX-NP.PG29 L15
PG36	25-33	15	47.0	37	50	HX-NP.PG36 L15
PG42	32-38	15	54.0	37	57	HX-NP.PG42 L15
PG48	37-44	18	59.3	38	64	HX-NP.PG48 L18

其他型号请参考 1-4 页
For other models, please refer to pages 1-4

金属电缆加长系列 Metal Cable Gland Series

