

金属耐高温电缆接头
Metal Cable Gland-High Temperature Resistance Type




M



材质：镍镀黄铜
密封件：三元乙丙、硅橡胶等
防水圈：三元乙丙、硅橡胶等
防水等级：IP68-10 巴压力
工作温度：静态：-60℃到 250℃

Material: Nickel-plated brass
Hermetic seal: EPDM, Silicone rubber
O-Ring: EPDM, Silicone rubber
Protection degree: IP68-10 bar
Temperature: Static state: -60 to 250℃



规格参数 单位: mm

专利产品
patented product

规格 Item	适用范围 Φ Range	螺纹长度 GL Thread Length	螺纹外径 AG Thread O.D.	接合长度 H Joint Length	扳手径 Spanner size	产品编号 Code
M8×1	2-5	5	8.0	13.5	12	HX-NGS.M8-5
M10×1.0	3-6.5	6.5	10.0	17	14	HX-NGS.M10-6.5
M12×1.5	3-6.5	6.5	12.0	17	14	HX-NGS.M12-6.5
M14×1.5	4-8	8	14.0	18	17	HX-NGS.M14-8
M16×1.5	4-8	8	16.0	19	18	HX-NGS.M16-8
M18×1.5	5-10	8	18.0	20	20	HX-NGS.M18-10
M20×1.5	8-12	8	20.0	21	22	HX-NGS.M20-12
M22×1.5	10-14	8	22.0	22	24	HX-NGS.M22-14
M24×1.5	10-14	9	24.0	22	24/27	HX-NGS.M24-14
M25×1.5	10-14	9	25.0	22	24/27	HX-NGS.M25-14
	12-16	9	25.0	25	27	HX-NGS.M25-16
	13-18	9	25.0	27	30/27	HX-NGS.M25-18
M27×1.5	13-18	9	27.0	27	30	HX-NGS.M27-18
M32×1.5	15-22	10	32.0	29	35	HX-NGS.M32-22
M36×1.5	18-25	10	36.0	31	40	HX-NGS.M36-25
M40×1.5	18-25	11	40.0	31	40/45	HX-NGS.M40-25
	22-30	11	40.0	35	45	HX-NGS.M40-30
M48×1.5	25-33	11	48.0	37	50/52	HX-NGS.M48-33
M50×1.5	32-38	13	50.0	37	57/55	HX-NGS.M50-38
M63×1.5	37-44	14	63.0	38	64/68	HX-NGS.M63-44



金属电缆接头系列
Metal Cable Gland Series