

金属管接式电缆接头
Metal Tubular Cable Glands



M / PG / G

CE ROHS IP68 REACH

材质: 镀镍黄铜
夹爪爪: 尼龙塑料 PA66, UL94-V2
密封件: 三元乙丙、硅橡胶等
防水圈: 三元乙丙、硅橡胶等
防水等级: IP68-10 巴压力
工作温度: 静态: -40°C 到 100°C, 短时间达 120°C
动态: -20°C 到 80°C, 短时间达 100°C

Material: Nickel-plated brass
Claw: IPA66 (Nylon), UL94-V2
Hermetic seal: EPDM, Silicone rubber
O-Ring: EPDM, Silicone rubber
Protection degree: IP68-10 bar
Temperature: Static state: -40 to 100°C, Short time to 120°C
Dynamic state: -20°C to 80°C, Short time to 100°C

Sealing Nut
迫紧螺母

Claw
夹紧爪

Seal
密封件

Body
主体

O-ring
O型圈

Lock Nut
螺母

规格参数 单位: mm

规格 Item	适用范围 Φ Range	螺纹长度 GL Thread Length	内螺纹 B Female thread	内螺纹深度 L1 Female thread depth	螺纹外径 AG Thread O.D.	接合长度 H Joint Length	扳手径 Spanner size	产品编号 Code
M12×1.5	3-6.5	6.5	M12×1.5	8	12.0	25	14	HX-NY.M12-6.5-M12
M16×1.5	4-8	8	M16×1.5	10	16.0	28	18	HX-NY.M16-8-M16
M20×1.5	6-12	8	M20×1.5	10	20.0	30	22	HX-NY.M20-12-M20
M25×1.5	12-16	9	M25×1.5	10	25.0	34	27	HX-NY.M25-16-M25
M32×1.5	15-22	10	M32×1.5	12	32.0	40	35	HX-NY.M32-22-M32
M40×1.5	22-30	11	M40×1.5	12	40.0	46	45	HX-NY.M40-30-M40
M50×1.5	32-38	13	M50×1.5	15	50.0	48	57/55	HX-NY.M50-38-M50
M63×1.5	37-44	14	M63×1.5	15	63.0	49	64	HX-NY.M63-44-M63

G1/2	6-12	8	G1/2	10	20.0	30	24/22	HX-NY.G1/2-12-G1/2
G3/4	13-18	9	G3/4	10	25.0	35	30	HX-NY.G3/4-18-G3/4
G1	15-22	10	G1	12	32.0	40	36	HX-NY.G1-22-G1
G1-1/4	22-30	11	G1-1/4	12	40.0	46	45	HX-NY.G1-1/4-30-G1-1/4
G1-1/2	32-38	13	G1-1/2	15	50.0	48	57/55	HX-NY.G1-1/2-38-G1-1/2
G2	37-44	14	G2	15	63.0	49	68/64	HX-NY.G2-44-G2

外接管螺纹尺寸支持定制 M/PG/G/NPT
Male thread sizes support custom M/PG/G/NPT



金属管接式电缆接头系列 Metal Cable Gland Series